



Filter type:	SL240 TRIO-CTN
Connection diameter:	3/4" or 1"
Average flow rate (m³/h):	0,5 at ΔP 0,2 bar
Working pressure (bar):	8
Max. operating pressure (bar):	12
Max. operating temperature (°C):	50
Weight (kg):	3,05 / 3,33 (with packaging)
Packaging in mm (L x W x H):	390 x 320 x 118
Quantity / pallet (units):	54
Filter head:	Polypropylene (PP)
Bowl:	SAN
Filtering support:	PP + 20% GF
Seals:	O-ring butadiene-acrylonitrile (NBR)
Centrifugal vane + cap:	Polyethylene (PE)
Wrench:	ABS
Filtering sleeve:	Polyester (non-washable) or nylon (washable)
Filtration surface + capacity:	440 cm² with sleeve + 0,57L with activated carbon
CTN container for activated carbon:	SAN (body) 0,6 mm + PP with 20% GF (cap) 0,3mm
Original equipment:	Filtering sleeve 100 μm + 25 μm, CTN filled with activated carbon, wrench, wall fixations in PP + 30% GF
Filtering fineness available (μm):	Non-washable : 1 - 5 - 10 - 25 - 50 - 100
(packs of 5 sleeves)	Washable : 150 - 300

