

WareDose 10 is a dosing system in a new SEKO outlook, with LED display, using potentiometers and DIP switches settings.

### FEATURES



- **Selectable power supply** 24 - 115 - 230 Vac
- **IP65** Protection degree and class II electrical insulation
- **ON/OFF** switch
- **Level Control Inputs.**
- **Analogic Speed Control (15-100%) of Det and Rinse pump via potentiometer on the board**
- **Manual Priming** of the pumps via buttons on frontal panel
- Features **new PC front cover with easy opening and stop in open position**
- New ABS polished enclosure with easy opening by frontal keys
- **3 Rollers and ball bearing** on motor shaft ensure 20% higher lifetime on tube and motor
- Robust plastic hinge not affected by corrosion.

### TECHNICAL FEATURES

TECHNICAL FEATURES	
TYPE	WareDose 10
CODE	WDO10040100Y0000
CERTIFICATIONS	CE, EAC
INTERFACE	Analogue with LED display
PROTECTION DEGREE	IP65
ELECTRICAL CLASS	Class II (ground connection not needed)
POWER SUPPLY	24 – 115 – 230 Vac (selectable by jumper)
CONSUMPTION	15 W
OPERATING TEMPERATURE	10-50°C
STORAGE TEMPERATURE	-20÷60°C
CASE MATERIAL	ABS

HYDRAULIC DATA	
DETERGENT PUMP FLOW RATE	1 - 4 l/h
RINSE AID PUMP FLOW RATE	0,15 – 1 l/h
RINSE PUMP MAX WORKING BACKPRESSURE	3 bar
DETERGENT PUMP SQUEEZE TUBE	Santoprene (6x10)
RINSE PUMP SQUEEZE TUBE	Sekobril (3x8)
EXTERNAL TUBE FITTINGS	For tube 4x6 with nuts (others upon request)

### DIMENSION

